


BoscoLighting's TETRIS Linear Downlight Series is designed to minimise glare and add style to your ceilings. Perfect for high-end residential projects or commercial applications. Available in a range of power levels, this simple fitting is suitable for cabinet lighting too.

Our products are easy to install, creating a pleasant feeling and good atmosphere.

*Trimless Version is newly added, please go to website to see the full range.







Features

- White trim with black reflector
- Easy installation
- LED Driver Included
- Supplied with Flex & Plug
- Available in 15°, 30°, 45° beam angle options
- CRI 92 available for anywhere extreme colour accuracy is required

Applications

- Museums & galleries
- Retail shops
- Bars & restaurants
- Residential and commercial projects

Recessed **Downlight TETRIS**





1x2W



2x2W



5x2W



10x2W



15x2W



Specs

Connect: AU Standard Flex & Plug Dimming: Non-dim, Trailing Edge, DALI






































BLSL-TETRIS-02

2W Mini Downlight Luminous Flux (lm): 200 CCT: Whites(3000K-5000K) Dimensions (mm): L45*W45*H49 Cutout(mm): L'37*W'37

Dimming: Non-dim Weight(kg): 0.12



BLSL-TETRIS-04

4W Twin Shop Light Luminous Flux (lm): 400 CCT: Whites(3000K-5000K) Dimensions (mm):L75*W45*H49 Cutout(mm): L'65*W'37 Dimming: Non-dim, Trailing Edge, DALI

Weight(kg): 0.24



BLSL-TETRIS-10

10W Linear Wall Washer Downlight Luminous Flux (lm): 1000 CCT: Whites(3000K-5000K) Dimensions (mm): L147*W45*H49 Cutout(mm): L'137*W'37 Dimming: Non-dim, Trailing Edge, DALI

Weight(kg): 0.35



BLSL-TETRIS-20

20W Linear Wall Washer Downlight Luminous Flux (lm): 2000 CCT: Whites(3000K-5000K) Dimensions (mm): L280*W45*H49 Cutout(mm): L'270*W'37

Dimming: Non-dim, Trailing Edge, DALI

Weight(kg): 0.54



BLSL-TETRIS-30

30W Linear Wall Washer Downlight Luminous Flux (lm): 2700 CCT: Whites(3000K-5000K) Dimensions (mm): L415*W45*H49 Cutout(mm): L'405*W'37

Dimming: Non-dim, Trailing Edge, DALI

Weight(kg):0.76